



If your compressor works more than 30 minutes per hour it means that it is too small. Please remember to drain the condensate at least once a week. Our technicians are at your disposal for any further information. All of our compressors are in accordance with EEC regulations.

ILLUSTRATION	DESCRIPTION	Suitable for:	Price	Code
	Silent Compressor HP 1/2 - 50/24 - Air intake: 50 lt/min - 24 liters tank - Watt 340 - Volt 220 - singlephase motor HP 0.5 - Maximum pressure 8 atm - Safety valve, pressure reducer - Manometer for pressure control with filter and 2 air exhausts - Automatic safe-engine - Noise: 40 decibel - Size: 400x400x600 mm - Net Weight 24 Kg - Gross 26 Kg.	Suitable for: 1 underpinner or 3-4 air guns	420	343
	Silent Compressor 2 motors HP 1 - 100/24 - Air intake: 100 lt/min - 24 liters tank - Watt 680 - Volt 220 - 2 singlephase motors HP 1 - Maximum pressure 8 atm - Automatic electric pressure switch, safety valve - Manometer for pressure control with filter and 2 air exhausts - Automatic safe-engine - Noise: 47 decibel - Size: 330x700x540 mm - Net Weight 39 Kg - Gross 42 Kg.	Suitable for: 1 underpinner or 1 pneumatic guillotine or 4-5 air guns	685	3431
	Silent Compressor 2 motors HP1 - 100/50 - Air intake: 100 lt/min - 50 liters tank - Watt 680 - Volt 220 - 2 singlephase motors HP 1 - Maximum pressure 8 atm - Automatic electric pressure switch, safety valve - Manometer for pressure control with filter and 2 air exhausts - Automatic safe-engine - Noise: 47 decibel - Size: 330x1050x570 mm. - Net Weight 50 Kg - Gross 57 Kg.	Suitable for: 1 underpinner or 1 pneumatic guillotine or 5-6 air guns	835	3432
	Silent Compressor SIL-AIR 150/50 by Werther - Air intake: 150 lt/min. - 50 liters tank - Watt: 1020 - Volt: 230 - 3 Singlephase motor HP 1 - Maximum pressure: 8 atm. - Manometer for pressure control - 2 Air exhausts - Pressure reducer - Safety valve - Automatic safe-engine - Noise: 49 decibel - Size: cm 40x86x75 - Net Weight 75 Kg - Gross 83 Kg	Suitable for: 2 underpinners or 1 pneumatic guillotine or 1 double mitre saw or 5/6 air guns	1.130	3433
	Silent Compressor SIL-AIR 200/10 by Werther - Air intake: 200 lt/min. - 100 liters tank - Watt: 1360 - Volt: 220 - 4 Singlephase motor HP 1 - Maximum pressure: 8 atm. - Manometer for pressure control - 2 Air exhausts - Pressure reducer - Safety valve - Automatic safe-engine - Noise: 49 decibel - Size: cm 40x127x65 - Net Weight 95 Kg - Gross 100 Kg	Suitable for: 2 underpinners or 1 pneumatic guillotine or 1 double mitre saw or 6/7 air guns	1.600	3434
	Non Silent Compressor Tiger 212 by Fini - Air intake: 200 lt/min. - 24 liters tank - Volt 230 - Singlephase motor HP 1.5 - 1 cylinder - Maximum pressure: 10 atm. - Automatic electric pressure switch, security valve - Manometer for pressure control, pressure reducer, air exhaust. - Noise: 77 decibel - Size: 650x310x600mm - Weight 25 Kg.	Suitable for: 1 underpinner 4-5 air guns Because of the noise, the compressor must be located in a different place of the laboratory.	130	345
	Non Silent Compressor Supertiger 262 by Fini - Air intake: 245 liters per minute - 50 liters tank - Singlephase motor HP 2 - 1 cylinder - Maximum pressure: 10 atm. - Automatic electric pressure switch, security valve - Manometer for pressure control, pressure reducer, air exhaust. - Noise: 79 decibel - Size: 880x350x650 mm - Weight 36 Kg.	Suitable for: 1 underpinner 1 pneumatic guillotine 5-6 air guns Because of the noise, the compressor must be located in a different place of the laboratory.	240	346

ACCESSORIES FOR COMPRESSORS

Illustration	Description	Price	Discount		Code	Illustration	Description	Price	Discount		Code			
			Q.ty	%					Q.ty	%				
	Tool Balancers The tool is raised over the bench, to be reached and brought down when needed.	for tools from 0,5 to 1,5 kg	19,00	3	6%	3501	Fitting with nut for bayonet connection 1/4"	male	1,10	3	10%	3480		
		for tools from 1,5 to 3 kg	21,00	3	6%	3502		female	1,10	3	10%	3481		
	Filter, 1/4"	19,00	3	6%	3471	<td>Central V-deviation, male, 1/4"</td> <td>1,80</td> <td>3</td> <td>10%</td> <td>3483</td>	Central V-deviation, male, 1/4"	1,80	3	10%	3483			
	Lubricator, 1/4"	25,00	3	6%	3472		Bayonet head, threaded, 1/4"	male	0,80	3	10%	3484		
	Filter regulator and manometer, 1/4"	39,00	3	6%	3473	female		0,80	3	10%	3484F			
	Filter/lubricator regulator unit for underpinners, 1/4"	66,00	3	6%	3474	<td>T-fitting for bayonet connection or threaded connection, 1/4"</td> <td>2,80</td> <td>3</td> <td>10%</td> <td>3485</td>	T-fitting for bayonet connection or threaded connection, 1/4"	2,80	3	10%	3485			
	Manometer, 1/4"	4,00	3	10%	3475		<td>Line cock, male-female, 1/4"</td> <td>3,90</td> <td>3</td> <td>10%</td> <td>3486</td>	Line cock, male-female, 1/4"	3,90	3	10%	3486		
<p>Our technicians are at your disposal for any further information</p> <td>Pressure regulator without filter, 1/4"</td> <td>26,00</td> <td>3</td> <td>6%</td> <td>3475R</td> <td rowspan="2"></td> <td>Tape in teflon to seal trimmings. mm 12x10 metres</td> <td>1,00</td> <td>3</td> <td>10%</td> <td>348T</td>	Pressure regulator without filter, 1/4"	26,00	3	6%	3475R			Tape in teflon to seal trimmings. mm 12x10 metres	1,00	3	10%	348T		
	Quick exhaust with spring, Italian profile, 6x8 mm	3,50	3	10%	3476			Oil for silent compressor. 1 liter bottle.	7,00	3	6%	343L		
	Quick coupling with spring, Italian profile, 6x8 mm	1,40	3	10%	3477			Fluid for nebulizers 1 litre bottle	9,00	3	6%	3487		
	Bayonet-shaped connection with spring, 6x8 mm	1,40	3	10%	3478			Coil nose, without connections. 30 meters long, 6x8 mm	23,00	3	6%	349		
	Quick coupling, Italian profile, threaded, 1/4"	male	0,80	3	10%	3479			Coil nose, with bayonet joint and connection.	5 mt long	8,00	3	6%	348R5
		female	0,80	3	10%	3479F	12 mt long			10,00	3	6%	348R12	
		Tube for compressed air. External diam: 8 mm Internal diam: 6 mm No connections.	5 mt pack	6,50	3	10%	3488		Coil nose, with bayonet joint and connection.	10 mt pack	10,00	3	10%	3488D
			50 mt pack	33,00	3	10%	3488F			100 mt pack	58,00	3	10%	3488C
			100 mt pack	58,00	3	10%	3488C							