

In these pages you will find various systems of hanging pictures. These systems are flexible and particularly suitable for galleries where you need to frequently change the pictures. By means of perlon, steel wires, rods and picture-hooks, frames can be hung at any desirable place and be switched easily. This system enables to hang and move pictures, without leaving behind unsightly (drilling) holes. Further information available on request.



ILLUSTRATION	DESCRIPTION	PACKING	PRICE per pack	Discounts		CODE		
				Q.ty	%			
	<p>The "Click Rail" is made of aluminum, 25 mm high and 8 mm wide. Supports a maximum weight of 30 kg per metre. To install the rail, you must first install the JS1D connectors to the wall using the screws wall plugs. Click and connectors must be ordered separately. It is advisable a connector every 40 cm. It is important that connectors are aligned horizontally. Price is per rail (not per metre).</p>	Matt white (can be painted) (RAL 9016)	2 mtrs long	5,80	5 10 20	10% 15% 20%	JS1A2	
		3 mtrs long	8,60	JS1A3				
		Alu brushed	2 mtrs long	5,80			JS1B2	
		3 mtrs long	7,90	JS1B3				
		White colour (RAL 9010)	2 mtrs long	5,70			JS1C2	
		3 mtrs long	8,50	JS1C3				
	<p>Clips used for fastening the "Click Rail" to walls and also for connecting several rails. Mount by means of screws and plugs every 40 cm. The rail is clicked onto the clips from the top side down.</p>	For even walls	50	6,80	5	10%	JS1D	
		For even and uneven walls	50	6,80	5	10%	JS1E	
	<p>Screw (flat-head 3,5x45 mm) with plug (6 mm universal). They are necessary to fix the clips JS1D and JS1E onto the wall.</p>	Screw	200	11,20	5	10%	JS1CV	
		Plug	100	4,10	5	10%	JS1CT	
	<p>End caps are used into both ends of the rail for a neat finish.</p>	White	2	1,40	6	10%	JS1F2	
		25	3,60	5	10%	JS1F		
		Grey	2	1,40	6	10%	JS1G2	
		25	3,60	5	10%	JS1G		
	<p>Corner connectors for a connection of lengths in inside as well as outside corners.</p>	White	2	1,40	6	10%	JS1L2	
		10	2,90	5	10%	JS1L		
		Grey	2	1,40	6	10%	JS1M2	
		10	2,90	5	10%	JS1M		
	<p>Kit containing all accessories for fixing one Click Rail to the wall and instruction sheet.</p>	Kit for white 2 mtrs Click Rail	2,10	5	10%	4065		
		Kit for white 3 mtrs Click Rail	2,70	5	10%	4061		
	<p>White rail "Click Rail" of 2 metres complete with all accessories: 6 connectors JS1D, 6 screws with plug, 2 end caps, 2 twister wires in perlon of 150 cm and 2 JS33 hooks.</p>	Matt white (can be painted)	2 mtrs long	11,60	3 8	8% 12%	JS1AK	
		Alu brushed	2 mtrs long	11,60			per type	JS1BK
	<p>Click Rail Pro It is an aluminum rail. It supports a maximum weight of 50 kg per metre. One of the characteristics of the "Click Rail Pro" consists in the fact that it can be mounted in two different ways, both in the normal way and upside down. The "normal" system has the advantage of hiding the metal block which is at the top. The "upside down" system, however, has the advantage of facilitating the alignment of the ceiling. The price is per rail (not per metre).</p>	Matt white (can be painted)	2 mtrs long	10,00	5 10 20	10% 15% 20%	JS4A2	
		3 mtrs long	14,50	JS4A3				
		Aluminum colour	2 mtrs long	10,00			per type	JS4L2
		3 mtrs long	14,50	JS4L3				
	<p>Clips used for fastening the Click Rail Pro to walls.</p>	White	20	4,60	5	10%	JS4DV	
		100	15,50	6	10%	JS4D		
	<p>Screw (flat-head 3,5x45 mm) with plug (6 mm universal). They are necessary to fix the clips JS1D, JS1E and JS4D onto the wall.</p>	Screw	200	11,20	5	10%	JS1CV	
		Plug	100	4,10	5	10%	JS1CT	
	<p>End caps used into the both ends of the rail Click Rail Pro.</p>	White	25	4,10	5	10%	JS4F	
		White	25	4,10	5	10%	JS4G	
	<p>Corner connectors for a connection of 2 Click Rail Pro.</p>	White	10	3,30	5	10%	JS4L	
		Grey	10	3,30	5	10%	JS4M	
	<p>Kit containing all accessories for fixing one Click Rail Pro to the wall and instruction sheet.</p>	Kit for white 2 mtrs Rail	2,65	5	10%	4067		
		Kit for white 3 mtrs Rail	3,20	5	10%	4074		
	<p>Perlon wire diameter 2 mm with loop. For this wire the rail it is not necessary. This wire has a loop that allows to hang it to a nail.</p>	Length 1 metre	0,65	10 50 100	15% 20% 25%	JS35		
		Length 2 metres	0,85			JS37		
		Length 3 metres	1,10			JS38		
	<p>Steel wire diameter 2 mm with loop. For this wire the rail is not necessary. This wire has a loop that allows to hang it to a nail.</p>	Length 1 metre	1,90	4975				
		Length 2 metres	2,60	4977				
		Length 3 metres	3,30	4979				
	<p>Perlon wire diameter 2 mm with slider. Insert it and slide it in the "Classic Rail" (with metal nipple JS36). Maximum weight: 15 kg.</p>	Length 2 metres	0,90	JS63				
		Length 3 metres	1,10	JS64				
	<p>Perlon wire diameter 2 mm with Twister-nipple. The perlon wire with Twister-nipple can be clicked in and out at any arbitrary place. After clicking it, it must be turned. Max weight: 20 kg.</p>	Length 1 metre	1,65	per type	JS781			
		Length 2 metres	1,90	JS782				
		Length 3 metres	2,20	JS783				
	<p>Steel wire diameter 1.8 mm with Twister-nipple. The steel wire can be used combined with alu rail and self-gripping hook code JS40 for heavy frames. Maximum weight: 15 kg.</p>	Length 1 metre	3,20	JS811				
		Length 1,5 metre	3,50	JS812				
		Length 2 metres	3,50	JS813				
		Length 2,5 metres	3,70	JS814				
	<p>White metal vertical rod with Twister-nipple. Max weight: 20 Kgs. Diameter 2 mm. It can be easily fixed to the rail in one move.</p>	Length 1 metre	4,40	JS96				
Length 2 metres		5,40	JS98					
Length 3 metres		3,80	JS815					
	<p>Wire coil. Used to obtain various length sizes. At the upper end of the wire you must fix the nipple JS42. The nipple JS42 will be inserted in the "Click Rail" so as not to be visible from the outside. Maximum weight: 10 Kg. Length 100 metres.</p>	Steel wire. Diameter 1 mm	14,50	3 10 25	10% 15%	JS41M		
		Steel wire. Diameter 1,5 mm	18,00			JS41B		
		Steel wire. Diameter 2 mm	12,60			JS41C		
	<p>Nipple nickel-plated to fasten to the perlon wire. Max weight 10 kg. Pack of 25 pieces.</p>		6,00	5	10%	JS42V		